



2 Mode Rotary Hammer





11 2 Mode Change Lever

Hammering with Rotation

Hammering





Slide Chuck



Compact 458mm

Tnakita. **II** No Hammering when Idling **::** Torque Limiter When drill bit hits No Hammering while Reinforcing bar idling because air in the against reinforcements, cylinder is not compressed Torque Limiter operates unless tool is pressed to stop the rotation of against ground.

Aluminum Housing

This function ensures

machine's long life.

Provides high quality and toughness.

drill bit, ensuring safety in vour work.



:: Rubberized Grip

Provides more comfort and control while minimizing hand fatigue and pain.

:: Auto Cut-Out Carbon Brush

When Carbon Brush wears out, it will automatically stop the motor. It protects commutator and indicates time for maintenance.

Comparison of Efficiency


Note: 1. It may differ under some conditions.
2. Numbers in the charts below are relative values

- when the capacities of Competitor "B" are indexed at 100.
- 1 Test conditions: Drilled in concrete with compressive strength of 40N/mm² to a depth of 40mm.
- 2 Test conditions: Chipped concrete with compressive strength of 40N/mm², and measured the amount of concrete removed.

1 Drilling (Bit diameter: 35mm)



2 Chipping



350

Rotary Hammer

Double Insulation

Torque Limiter Carrying Case





HR4002 40mm (1-9/16")

Continuous rating Input 1,050W (10A: North America) Max. bit dia. 40mm (1-9/16") Max. core bit dia. 105mm (4-1/8") Blows per minute 2,500bpm No load speed 680rpm 458mm x 114mm x 256mm (18" x 4-1/2" x 10-1/8") Dimensions $(L \times W \times H)$ 6.2kg (13.7lbs) Net weight 5.0m (16.4ft) Power supply cord

Standard Equipment

Depth Gauge, Grip Assembly, Grease Vessel (Tool does not come with bit)

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan